

FÜLLVORLACK

Füllvorlack, lösemittelhaltig, für innen und aussen

Technical information Version

(1.0) 02/26



swiss  quality

Lösemittelhaltiger Vorlack auf Kunstharzbasis für innen und aussen. Vorzügliches Füllvermögen und ausgezeichnete Deckkraft sowie hoher Dauerelastizität.

Beschreibung

Areas of application Im Innen- und Aussenbereich für Fenster, Türen, Schränke, Täfer usw. wo Wert auf eine hohe Füllkraft gelegt wird.

Core data

Properties	Delivery viscosity	Pasty (stir well before use)
	Density	Approx. 1.52 kg/l
	Solid state	Ca. 74% (Weiss)
	Gloss level	Silk matt
	Flash point	36 °C
	Shades (stock shades)	White
	Tintable	Mit DoldColorSystem, Handabtönungen bis max. 3% mit geeigneten Universalabtönpasten möglich
	Storage life	Store in tightly closed original container for 1 year at 5 - 25°C.
	Processing temperature	Do not process below + 5°C (object temperature), ideal temperature range 15 - 22°C.
		Protect from direct sunlight.
	Adhesive strength	Gt 0-1 (DIN EN ISO 2409)
	Environmental label	F
	Highlight	Ausgezeichnete Füllkraft

Substrate / Processing

Substrates	Der Untergrund muss den üblichen Anforderungen entsprechend rost-, fett-, öl-, zunderfrei, sauber und trocken sein. Je nach Art des Untergrundes (Metall, Holz, Kunststoff) müssen geeignete Vorbehandlungen, Grundierungen eingesetzt werden.
Application	Brushing and rolling Streich- und rollfertig, 0 - 5% mit Streichverdünner verdünnbar.
	Airless spraying 10 - 20% mit Universalverdünner verdünnbar.

Drying	<p>Dust-dry (TG1) After approx. 2 - 3 hours</p> <p>Reworkable After approx. 24 hours</p> <p>Fully dried After approx. 48 hours</p> <p>Die Trocknung ist von der relativen Luftfeuchtigkeit, der Luft- und Objekttemperatur und der Schichtdicke abhängig. Die ermittelten Angaben entsprechen den Normbedingungen bei 20°C Raumtemperatur und 65% relativer Luftfeuchtigkeit.</p>
Coverage	<p>8 – 10 m²/kg</p> <p>9 – 13 m²/l</p> <p>Der Verbrauch ist von der Applikationsart, der Struktur des Untergrundes und der erzielten Schichtdicke abhängig. Die angegebenen Werte sind Durchschnittszahlen aus der Praxis.</p>
Tool cleaning	Clean immediately and thoroughly with thinner (e. g. universal or cellulose thinner).

Information

Hazard warnings	For further information see the corresponding EU safety data sheet.
Further information	The SMGV information sheets and the FSO guidelines must be observed.
Important	Wir empfehlen bei Bauteilen wie z.B. Türen, Zargen etc. vorgängig Musterflächen anzulegen.

Quality and environment



With the environmental label, coating materials can be identified in a transparent and clear scheme according to environmental and health protection criteria, as well as suitability for use. The environmental label creates transparency for the builder, architect, planner and client. All products of Dold AG are classified in the category A to G.



Dold AG was founded on August 01, 1921 by Hans Dold in Wallisellen. Until Dold is still located at the same site and is one of the leading paint and varnish manufacturers in paint manufacturers in Switzerland. In Wallisellen, Dold AG develops and manufactures its innovative range of paints and varnishes for the construction painter as well as for industrial customers.



Swiss paint and varnish factory certified according to ISO 9001 / 14001 / 45001. Dold AG is one of the few one of the few paint and varnish factories which not only has its quality management, management, but also its environmental management system, as well as the occupational safety and health protection processes have been certified. These certifications are a clear commitment for Dold AG towards all its commitment to all its stakeholders.



Environmentally friendly products are a concern for DOLD. The foundation KMU Klima confirms Dold AG's contribution to voluntary climate protection. For this concern all direct emissions of CO₂ in form of electricity, heating and mobility are compensated by DOLD to a reforestation project in Uruguay. This is a long-term contribution to climate protection and for the sake of the environment.

The above information is for general guidance only. The working conditions beyond our control and the large number of different substrates mean that no claims can be made on the basis of this information. In case of doubt, we recommend that you carry out sufficient tests yourself. A guarantee can only be given for the consistently high quality of our products. All previous editions of this data sheet hereby lose their validity.