

HOLZGRUNDIERUNG

Weisse Holzgrundierung zum Tauchen und Streichen,
lösemittelhaltig, für aussen

Technical information Version
(1.0) 02/26



swiss  quality

Dold Holzgrundierung ist eine nach modernsten Erkenntnissen aufgebaute Holzgrundierung mit ausgeprägter Tiefenwirkung und "ventilierenden" Eigenschaften. Sie lässt sich streichen, tauchen und fluten. Sie ist mit Filmschutz für algen- und pilzgefährdete Flächen ausgestattet.

Beschreibung

Areas of application Baualerei, Fensterfabrikation, Holzindustrie. Regulierung des Feuchtigkeitshaushaltes, gute Haftvermittlung für die weiteren Anstrichschichten. Wird eingesetzt für Fenster, Türen, Rahmen, Rollläden, Jalousien, Holzkonstruktionen der Vorfabrikation usw. Auch abgelagte, trockene Holzobjekte werden damit rationell tauchgrundiert oder geflutet.

Core data

Properties	Delivery viscosity	Pasty (stir well before use)
	Density	Approx. 1.34 kg/l
	Solid state	Ca. 70 % (Weiss)
	Gloss level	Matt
	Flash point	36 °C
	Shades (stock shades)	White
	Tintable	Nicht abtönbar mit DoldColorSystem, Handabtönungen bis max. 3 % mit geeigneten Universalabtönpasten möglich
	Storage life	Store in tightly closed original container for 1 year at 5 - 25°C.
	Processing temperature	Do not process below + 5°C (object temperature), ideal temperature range 15 - 22°C.
		Protect from direct sunlight.
	Adhesive strength	Gt 0-1 (DIN EN ISO 2409)
	Environmental label	F
	Highlight	Ausgezeichnete Tiefenwirkung und ventilierende Eigenschaften

Substrate / Processing

Substrates Der Untergrund muss den üblichen Anforderungen entsprechend sauber und trocken sein. Die Holzfeuchtigkeit darf maximal 15% betragen.

Quality and environment



With the environmental label, coating materials can be identified in a transparent and clear scheme according to environmental and health protection criteria, as well as suitability for use. The environmental label creates transparency for the builder, architect, planner and client. All products of Dold AG are classified in the category A to G.



Dold AG was founded on August 01, 1921 by Hans Dold in Wallisellen. Until Dold is still located at the same site and is one of the leading paint and varnish manufacturers in paint manufacturers in Switzerland. In Wallisellen, Dold AG develops and manufactures its innovative range of paints and varnishes for the construction painter as well as for industrial customers.



Swiss paint and varnish factory certified according to ISO 9001 / 14001 / 45001. Dold AG is one of the few one of the few paint and varnish factories which not only has its quality management, management, but also its environmental management system, as well as the occupational safety and health protection processes have been certified. These certifications are a clear commitment for Dold AG towards all its commitment to all its stakeholders.



Environmentally friendly products are a concern for DOLD. The foundation KMU Klima confirms Dold AG's contribution to voluntary climate protection. For this concern all direct emissions of CO₂ in form of electricity, heating and mobility are compensated by DOLD to a reforestation project in Uruguay. This is a long-term contribution to climate protection and for the sake of the environment.

The above information is for general guidance only. The working conditions beyond our control and the large number of different substrates mean that no claims can be made on the basis of this information. In case of doubt, we recommend that you carry out sufficient tests yourself. A guarantee can only be given for the consistently high quality of our products. All previous editions of this data sheet hereby lose their validity.